



Safety Data Sheet

I. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PRIME GUARD UTF 55GL
Product Code: PF04HT55 PGUTF55
Emergency Phone: CHEMTREC: +1 (800) 424-9300
 International: +01 (703) 527-3887
Poison Control Center: (800) 222-1222
Company: Prime Guard
 8295 Tournament Dr. Ste 150
 Memphis, TN 38125
Information Phone: (662) 874-1283
E-mail: sds@wd-wpp.com

II. HAZARDS IDENTIFICATION

Routes of Entry: Skin contact
Target Organs: Skin, Eyes, Respiratory Tract, Lungs
Chemical Interactions: No chemical interaction known to affect toxicity.
Conditions Aggravated by Exposure: Personnel with pre-existing skin disorders should avoid contact with this product., Lung disease, Skin disease including eczema and sensitization, Respiratory disease including asthma and bronchitis, Eye disease

Acute Health Effects:

Inhalation Irritation: Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.
Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage. May cause skin irritation.
Skin Absorption: No absorption hazard in normal industrial use.
Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Ingestion Irritation: Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

Chronic Health Effects:

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.
Reproductive Toxicity: No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

HMIS Ratings:

Health: 2
 Fire: 1
 Reactivity: 0
 PPE: B

NFPA Ratings:

Health: 2
 Fire: 1
 Reactivity: 0

KEY: 0 - Least 1 - Slight 2 - Moderate 3 - High 4 - Extreme

III. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	%	CAS #	OSHA Exposure Limits
Petroleum distillates, hydrotreated heavy paraffinic	90 - 99	64742-54-7	5 mg/m3
Mineral oil	0.1 - 1	8012-95-1	5 mg/m3 TWA

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

Safety Data Sheet

IV. FIRST-AID MEASURES

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.
Eyes:	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Seek medical advice if symptoms persist.
Ingestion:	Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal. Contains a harmful substance. Seek medical help immediately and contact a poison information service. Drink two glasses of water or milk to dilute.
Notes to Doctor:	Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to cause aspiration.

V. FIRE FIGHTING MEASURES

Flammability	Combustible at elevated temperatures
Summary:	
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
Fire and/or Explosion Hazards:	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
Fire Fighting Methods and Protection:	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.
Hazardous Combustion Products:	Carbon monoxide, Smoke

VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
Methods for Clean-up:	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center. Remove from water surface by skimming or with suitable absorbents. Do not use dispersants. Avoid runoff into storm sewers and ditches that lead to waterways. Do not flush to sewer.

VII. HANDLING AND STORAGE

Handling Precautions:	Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Empty containers may retain product residues/ vapors. Use proper bonding and grounding during bulk product transfer.
Storage Conditions:	Store in a cool dry place. Isolate from incompatible materials.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:	No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. Engineering controls must be designed to meet the OSHA chemical specific
------------------------------	--

Safety Data Sheet

standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Facilities storing or using this material should be equipped with an eyewash and safety shower.

Respiratory Protection: Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. Wear a NIOSH approved respirator if any exposure is possible.

Respirator Type(s): None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses. Wear goggles and a Face shield.

Skin Protection: Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

Gloves: Neoprene, Nitrile

Control Parameters:

Chemical Name	ACGIH TLV -TWA	ACGIH STEL	IDLH	NIOSH STEL
Petroleum distillates, hydrotreated heavy paraffinic Mineral oil	5 mg/m3	10 mg/m3	2500 mg/m3 IDLH	10 mg/m3 STEL
	TWA (excluding metal working fluids, highly & severely refined, inhalable fraction)			

X. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Brown
Odor:	Mild
pH:	Not determined
Viscosity (cSt at 40°C):	63.22
Solubility in Water:	Negligible; 0-1%
Octanol/Water	Not determined
Partition Coefficient:	
Evaporation Rate:	Not determined
Vapor Density:	Not determined
Vapor Pressure:	<0.20
Boiling Point (°C):	Not determined
Freezing Point (°C):	Not determined
Specific Gravity:	0.87
Density:	7.23
Flash Point (°C):	224
Flash Point Method:	COC
Upper Flammability	= 10

Safety Data Sheet

Limit, % in air:
Lower Flammability = 1
Limit, % in air:

X. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Hazardous polymerization will not occur
Conditions to Avoid: Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Moisture (will lead to product performance degradation).
Materials to Avoid: Strong oxidizing agents
Hazardous Decomp. Products: Carbon monoxide, Smoke
Hazardous Polymerization: Hazardous polymerization will not occur.

XI. TOXICOLOGICAL INFORMATION

Acute Toxicity:

Ingestion: Although this product has a low order of acute oral toxicity, aspiration of minute amounts into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.
Inhalation: Harmful! Can cause systemic damage (see "Target Organs").
Absorption: No absorption hazard in normal industrial use.
Eyes: This material is estimated to be non-irritating eyes (Draize score <15 [rabbits]).
Skin: This material is estimated to be slightly irritating (Primary Irritation Index is 0.5 - 3.0 [rabbits]).
Sensitization: No data available to indicate product or components may be a skin sensitizer.

Component Toxicology Data:

Chemical Name	CAS #	LD ₅₀ /LC ₅₀
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Inhalation LC ₅₀ Rat 2.18 mg/L 4 h; Oral LD ₅₀ Rat >2000 mg/kg; Dermal LD ₅₀ Rabbit >2000 mg/kg
Mineral oil	8012-95-1	Inhalation LC ₅₀ Rat 2062 ppm 4 h (Source: NLM_CIP)

XII. ECOLOGICAL INFORMATION

Overview: Slight ecological hazard. In high concentrations, this product may be dangerous to plants and/or wildlife.
Mobility: This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.
Persistence: Biodegradation, adsorption to sediment, and bioconcentration to aquatic organisms should not be significant.
Bioconcentration: Bioconcentration may occur.
Degradability: Biodegrades slowly.

Toxicity to Aquatic Invertebrates:	CAS #	Results
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	48 Hr EC ₅₀ Daphnia magna: >1000 mg/L

Toxicity to Fish:	CAS #	Results
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	96 Hr LC ₅₀ Oncorhynchus mykiss: >5000 mg/L

Safety Data Sheet

XIII. DISPOSAL CONSIDERATIONS

Disposal of Packaging: Recycle containers whenever possible.
Disposal Methods: Dispose of according to Federal, State, Local, or Provincial regulations. Recycle used oil.

XIV. TRANSPORTATION INFORMATION

D.O.T. Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO).

XV. REGULATORY INFORMATION

TSCA Status: All components of this material are on the US TSCA Inventory or are exempt.
State Restrictions: Not applicable
WHMIS: Uncontrolled product according to WHMIS classification criteria

Chemical Name	Regulation	CAS #	% Range
None.	CERCLA RQ		
Diethanolamine	SARA 313	111-42-2	0.001- 0.01
Vinyl acetate	SARA 313	108-05-4	0.001- 0.01
Cumene	SARA 313	98-82-8	0.001- 0.01
Naphthalene	SARA 313	91-20-3	<10ppm
Arsenic	SARA 313	7440-38-2	<10ppm
Methyl isobutyl ketone	SARA 313	108-10-1	<10ppm
Toluene	SARA 313	108-88-3	<10ppm
Benzene	SARA 313	71-43-2	<10ppm
Cadmium	SARA 313	7440-43-9	<10ppm
ethylbenzene	SARA 313	100-41-4	<10ppm
None.	SARA 302-EHS		
None.	TSCA 12b export notification		
2,2'-Iminodiethanol	CA Prop 65 – Cancer	111-42-2	0.001- 0.01
Cumene	CA Prop 65 – Cancer	98-82-8	0.001- 0.01
Naphthalene	CA Prop 65 – Cancer	91-20-3	<10ppm
ISOBUTYL METHYL KETONE	CA Prop 65 – Cancer	108-10-1	<10ppm
Benzene	CA Prop 65 – Cancer	71-43-2	<10ppm
Cadmium	CA Prop 65 – Cancer	7440-43-9	<10ppm
ethylbenzene	CA Prop 65 – Cancer	100-41-4	<10ppm
Toluene	CA Prop 65 - Dev. Toxicity	108-88-3	<10ppm
Benzene	CA Prop 65 - Dev. Toxicity	71-43-2	<10ppm
Cadmium	CA Prop 65 - Dev. Toxicity	7440-43-9	<10ppm
Toluene	CA Prop 65 - Reprod –fem	108-88-3	<10ppm
Benzene	CA Prop 65 - Reprod –male	71-43-2	<10ppm
Cadmium	CA Prop 65 - Reprod –male	7440-43-9	<10ppm
Mineral oil	Canadian WHMIS List	8012-95-1	0.1 - 1
Oil, mineral	Massachusetts RTK List	8012-95-1	0.1 - 1
Mineral oils, highly-refined	New Jersey RTK List	8012-95-1	0.1 - 1
Mineral oil	Pennsylvania RTK List	8012-95-1	0.1 - 1
Oil mist, mineral	Minnesota Hazardous Substance List	8012-95-1	0.1 - 1

Safety Data Sheet

Consumer Product Safety Improvement Act of 2008 General Conformity Certification:

This product has been evaluated and certified to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

XVI. ADDITIONAL INFORMATION

Supersedes: 8/27/2014 4:42:06 PM

Revision Date: 9/4/2014 12:20:34 PM

Disclaimer: This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.